

Magnetic Sensor ICs
South Unipolar Detection High Performance Low Power Hall-Effect Sensor IC

AS1812B
● General Description

Using low power CMOS process, the AS1812B is designed for low power, high performance unipolar detection hall-effect application, such as cover switch, contactless switch, solid state switch and lid close sensor etc battery operation. The hall IC integrated an on-chip hall voltage generator for magnetic sensing, a comparator that amplifiers the hall voltage, a Chopper amplifier, a Schmitt trigger to provide switching hysteresis for noise rejection, and a complementary output.

The total power consumption of AS1812B is typically less than 1.0uA at 1.8V power supply. AS1812B is designed to respond to alternating South pole. When the magnetic flux density (B) is larger than operate point (B_{OPS}), the output will be turned on (low), the output is held until the magnetic flux density (B) is lower than release point (B_{RPS}), then turn off (high).


The device is available in DFN1216-4L, DFN1010-4L and SIP-3L Package and is rated over the -40°C to 85°C. The package is RoHS and Green compliant.

● Features

- Input Voltage Range : 1.65V to 5.5V
- Micro-power consumption ideal for battery power applications
- Uniplar Operation, easy to use as output
- Very high sensitivity hall sensor
- Low Power CMOS process technology
- Chopper stabilization amplifier stage
- Magnetic Sensitivity (typical)
 $B_{OPS}=40\text{Gauss}$, $B_{RPS}=25\text{Gauss}$
- Good RF noise immunity
- No need pull-up resistor
- Small Solution Size
- RoHS & Green Compliant
- DFN1216-4L, DFN1010-4L and SIP-3L Package
- -40°C to +85 °C Temperature Range

● Applications


- Cover switch in clam-shell cellular phones
- Cover switch in Notebook, PC/PAD
- Contact-less switch in consumer products
- Solid State Switch
- Handheld Wireless Handset Awake Switch
- Lid close sensor for battery-powered devise
- Magnet proximity sensor for reed switch replacement in low duty cycle applications
- DV, DSC, and White Goods

■ Ordering Information
AS1812BXXX


Part Number	B_{OPS} (Gauss)	B_{RPS} Gauss)	Package Type	Package Qty	Temperature	Eco Plan
AS1812BD4RN	40	25	DFN1216-4L	7-in reel 3000pcs/reel	-40~85°C	Green
AS1812BD1RN	40	25	DFN1010-4L	7-in reel 3000pcs/reel	-40~85°C	Green
AS1812BMBN	40	25	SIP-3L	1000pcs/Package	-40~85°C	RoHS
AS1812BD4RY	40	25	DFN1216-4L	7-in reel 3000pcs/reel	-40~125°C	Green
AS1812BD1RY	40	25	DFN1010-4L	7-in reel 3000pcs/reel	-40~125°C	Green
AS1812BMBY	40	25	SIP-3L	1000pcs/Package	-40~125°C	RoHS


■ Marking & Pin Assignment

DFN1216-4L (Top View):




Pin Name	Pin No.	I/O	Pin Function
	DFN1216-4L		
VDD	2	P	Input Power Supply
GND	4	P	Ground
NC	3	-	Not Connected
OUTPUT	1	O	Output Pin

DFN1010-4L (Top View):



Pin Name	Pin No.	I/O	Pin Function
	DFN1010-4L		
VDD	2	P	Input Power Supply
GND	4	P	Ground
NC	3	-	Not Connected
OUTPUT	1	O	Output Pin

SIP-3L:



Pin Name	Pin No.	I/O	Pin Function
	SIP-3L		
VDD	1	P	Input Power Supply
GND	2	P	Ground
OUTPUT	3	O	Output Pin.

■ Typical Application Circuit




Figure 1, Typical Application Circuit of AS1812B

■ Block Diagram




Figure 3, Block Diagram of AS1812B

■ Absolute Maximum Ratings¹ (T_A=25°C, unless otherwise noted)

Parameter		Symbol	Rating	Unit
V _{DD} Pin to GND		V _{DD}	-0.3 to 6.0	V
Output Pin to GND		V _{OUTPUT}	-0.3 to V _{DD} +0.3	V
Max. Continuous Output Current		I _{OUTMAX}	2.0	mA
Magnetic Flux Density		B	Unlimited	Gauss
Package Power Dissipation	DFN1216-4L/DFN1010-4L	P _D	250	mW
	SIP-3L		400	
Storage Temperature Range		T _S	-55 to +150	°C
Operating Junction Temperature Range		T _{OP}	-40 to +150	°C
Maximum Soldering Temperature (at leads, 10 sec)		T _{LEAD}	300	°C

■ Recommended Operating Conditions²

Parameter	Symbol	Rating	Unit
V _{DD} Pin to GND	V _{DD}	1.65 to 5.5	V
Continuous Output Current	I _{OUT}	1.0	mA
Operating Temperature Range	T _{OP}	-40 to +85	°C

Note: 1: Stresses above those listed in absolute maximum ratings may cause permanent damage to the device. Functional operation at conditions other than the operating conditions specified is not implied. Only one absolute maximum rating should be applied at any one time.

2: The device is not guaranteed to function outside of its operating conditions.

■ Electrical Characteristics

($T_A = -40$ to $+85^\circ\text{C}$ unless otherwise noted. Typical values are at $T_A = +25^\circ\text{C}$, $V_{DD} = 1.8\text{V}$)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_{DD}	Input Voltage		1.65	1.8	5.5	V
$I_{DD}(\text{AVG})$	Supply Current	Average supply current, $T_A = 25^\circ\text{C}$, $V_{DD} = 1.8\text{V}$	-	1.0	2.0	μA
$I_{DD}(\text{AVG})$		Average supply current, $T_A = 25^\circ\text{C}$, $V_{DD} = 3.65\text{V}$	-	2.0	4.0	μA
T_{awake}	Awake Time		-	30	-	μs
T_{period}	Period		-	100	150	ms
D.C.	Duty Cycle		-	0.03	-	%
V_{OH}	Output Off Voltage (High side)	$I_{OUT} = +1\text{mA}$	$V_{DD} - 0.3$	$V_{DD} - 0.1$	$V_{DD} + 0.3$	V
V_{OL}	Output On Voltage (Low side)	$I_{OUT} = -1\text{mA}$	-0.3	0.1	+0.3	V
Magnetic Para.						
B_{OPS}	Magnetic Operating Point		-	40	50	Gauss
B_{RPS}	Magnetic Release Point		10	25	-	Gauss
B_{HYS}	Hysteresis Window		-	15	-	Gauss





Fig 4, Magnetic Operation Characteristic of AS1812B

■ Function Description



Micro-power Operation

Internal timing circuitry activates the sensor for $30\mu s$ and deactivates it for the remainder of the period (100ms). A short "awake" time allows for stabilization prior to the sensor sampling and data latching on the falling edge of the timing pulse. The output during the "sleep" time is latched in the last sampled state. The supply current is not affected by the output state.

Chopper-Stabilized Technique

The Hall element can be considered as a resistor array similar to a Wheatstone bridge. A large portion of the offset is a result of the mismatching of these resistors. These devices use a proprietary dynamic offset cancellation technique, with an internal high-frequency clock to reduce the residual offset voltage of the Hall element that is normally caused by device over-molding, temperature dependencies, and thermal stress. The chopper-stabilizing technique cancels the mismatching of the resistor circuit by changing the direction of the current flowing through the Hall plate using CMOS switches and Hall voltage measurement taps, while maintains the Hall voltage signal that is induced by the external magnetic flux. The signal is then captured by a sample-and-hold circuit and further processed using low-offset bipolar circuitry. This technique produces devices that have an extremely stable quiescent Hall output voltage, are immune to thermal stress, and have precise recoverability after temperature cycling. A relatively high sampling frequency is used for faster signal processing capability can be processed.


Magnetic Field Detection Mechanism

The Hall IC cannot detect magnetic fields that run horizontal to the package top layer. Be certain to configure the Hall IC so that the magnetic field is perpendicular to the top layer.

Operation

The output of this device switches low (turns on) when a magnetic field perpendicular to the Hall sensor exceeds the operate point B_{OPS} . After turn-on, the output is capable of sinking up to 1mA and the output voltage is $V_{OUT}(ON)$. When the magnetic field is reduced below the release point B_{RPS} , the device output switches high (turns off). The difference between the magnetic operates and release points are the hysteresis (B_{HYS}) of the device. This built-in hysteresis allows clean switching of the output even in the presence of external mechanical vibration and electrical noise.

Applications:



AS1812B's pole-independent sensing technique allows for operation with south pole magnet orientation, enhancing the manufacturability of the device.

C1 serves two purposes: minimizing ripples on the input voltage and enhancing immunity from RF transmission noises within close proximity. Recommended values are between 10nF and 100nF. The larger the capacitance, the better the noise immunity is for the AS1812B.

It is strongly recommended that an external bypass capacitor be connected (in close proximity to the Hall sensor) between the supply and ground of the device to reduce both external noise and noise generated by the chopper-stabilization technique. This is especially true due to the relatively high impedance of battery supplies. The simplest form of magnet that will operate these devices is a bar magnet with south pole near the branded surface of the device.

Thermal Considerations


The maximum IC junction temperature should be restricted to 125°C under normal operating conditions. This restriction limits the power dissipation of the AS1812B. Calculate the maximum allowable dissipation, $P_{D(max)}$, and keep the actual dissipation less than or equal to $P_{D(max)}$. The maximum-power-dissipation limit is determined using following equation:

$$P_{D(MAX)} = \frac{125^{\circ}\text{C} - T_A}{R_{\theta JA}}$$

Where, T_A is the maximum ambient temperature for the application. $R_{\theta JA}$ is the thermal resistance junction-to-ambient given in Power Dissipation Table.


■ Package Information

DFN1216-4L:




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.320	0.400	0.013	0.016
A1	0.000	0.050	0.000	0.002
A3	0.102 (BSC)		0.004 (BSC)	
D	1.500	1.700	0.059	0.067
E	1.100	1.300	0.043	0.051
D1	0.440	0.640	0.017	0.025
E1	0.440	0.640	0.017	0.025
L	0.150	0.250	0.006	0.010
b	0.150	0.250	0.006	0.010
b1	0.150 (BSC)		0.006 (BSC)	
e	0.650 (BSC)		0.026 (BSC)	
k	0.330 (BSC)		0.013 (BSC)	

DFN1010-4L:




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.340	0.400	0.014	0.016
A1	0.000	0.050	0.000	0.002
A3	0.152 BSC		0.006 BSC	
D	0.950	1.050	0.038	0.042
E	0.950	1.050	0.038	0.042
D1	0.450	0.550	0.018	0.022
E1	0.450	0.550	0.018	0.022
k	0.211 BSC		0.008 BSC	
b	0.180	0.280	0.0072	0.0112
e	0.625 BSC		0.025 BSC	
L	0.200	0.300	0.008	0.012

SIP-3L:


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.900	3.100	0.114	0.122
b	0.350	0.560	0.014	0.022
b1	0.440 (BSC)		0.017 (BSC)	
C	0.360	0.510	0.014	0.020
D	3.900	4.100	0.153	0.161
E	1.420	1.620	0.056	0.064
E1	0.750 (BSC)		0.030 (BSC)	
e	1.270 (BSC)		0.050 (BSC)	
e1	2.540 (BSC)		0.100 (BSC)	
L	13.500	15.500	0.531	0.610
L1	1.600 (BSC)		0.063 (BSC)	
$\theta 1$	6°		6°	
$\theta 2$	6°		6°	
$\theta 3$	6°		6°	
$\theta 4$	6°		6°	
X	1.900	2.100	0.075	0.083
Y	0.850	0.950	0.033	0.037

■ Packing Information



Package Type	Carrier Width(W)	Pitch(P)	Reel Size(D)	Packing Minimum	Pin1 Quadrant
DFN1216-4L	8.0±0.1 mm	4.0±0.1 mm	180±1 mm	3000pcs	Q2
DFN1010-4L	8.0±0.1 mm	4.0±0.1 mm	180±1 mm	10000pcs	Q1

Note: Carrier Tape Dimension, Reel Size and Packing Minimum

■ Packing Information

SIP-3L:

1, Packing type: Bulk

2, Packing minimum: 1000pcs